

ECLIPSE ACOUSTIC

TECHNICAL DATA

CERTIFICATION & CLASSIFICATION	STANDARDS	ECLIPSE ACOUSTIC
Type of floor covering	ISO 11638	Homogeneous vinyl flooring with foam interlayer
Classification	EN ISO 10874	Commercial: 34 Industrial: 42
Wear layer binder content	ISO 11638	Type II

TECHNICAL CHARACTERISTICS		
Total thickness	EN ISO 24346	3.7 mm
Total weight	EN ISO 23997	3600 g/m ²
Wear layer thickness	EN ISO 24340	2.0 mm
Foam layer thickness	EN ISO 24340	1.5 mm
Adhesive foil thickness	EN ISO 24340	0.2 mm
Surface treatment		PUR reinforced
Form of delivery	EN ISO 24341 Sheet (rolls)	Approx. 23 lm x 195 cm Art. no. 21085 ___ 3 digit colour number

PERFORMANCES FOR CE MARKING REQUIREMENTS (EN 14041)		
Declaration of Performance	EN 14041 EN 13501-1	0019-0050-DoP-2013-07 Class B _{fl} -s1
Reaction to fire	EN ISO 9239-1 EN ISO 11925-2	≥ 8 kW/m ² Pass
Thermal resistance	EN 12667/DIN 52612	Approx. 0.01 m ² K/W
Slip resistance	EN 13893 /BS 7976-2	≥ 0.3 / Low risk of slip

TECHNICAL PERFORMANCES		
Residual indentation	EN ISO 24343-1	Required value: ≤ 0.20 mm
Impact sound reduction	EN ISO 717/2	Approx. + 17 dB
Slip resistance	DIN 51130	R9
Clean room test	ASTM F24 F51 ISO 14644-1	Class A ISO class 4
Ease of decontamination	ISO 8690	Good
Bacteria resistance	EN ISO 846: Part C	Does not favour growth
Chemical resistance	ISO 26987	Good resistance
Castor chair	ISO 4918	Suitable
Flexibility	ISO 24344	Pass
Dimensional stability	EN ISO 23999	≤ 0.40 % for rolls
Light fastness	EN ISO 105-B02	≥ 6
Seam strength	EN 684	Average value: ≥ 240 N/50 mm Individual values: ≥ 180 N/50 mm
Underfloor heating		Suitable - max. 27°C

ENVIRONMENTAL PERFORMANCES		
Total VOC emissions	ISO 16000-9 / Indoor air quality	≤ 10 µg/m ³ (after 28 days) / Platinum

COLOURS

12

The above information is subject to modification for the benefit of further improvement. (04/18).

According to the European Regulation N° 305/2011 for CE Marking, the Declarations of Performance are available on our website www.tarkett.com

Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.

Colours of the products shown in the photos or samples are indicative only. There may be differences in colours, gloss and embossing structure between the products sold and photos or samples.

CUSTOMS TARIFF : 4820 5000 00

