












CERTIFICATION AND CLASSIFICATION Universe

CE certification	EN 14041:2004/AC:2006	2701-0068-DoP-2021-11
Classification	ISO 10874 (EN 685)	  Commercial: 34 Industrial: 43

TECHNICAL CHARACTERISTICS Universe

TECHNICAL CHARACTERISTICS	STANDARD	Universe
Extreme protection PUR reinforcement		yes
Total thickness	ISO 24346 (EN 428)	 2,0 mm
Wear layer thickness	ISO 24340 (EN 429)	 0,70 mm
Total weight	ISO 23997 (EN 430)	 2,22 kg/m ²
Form of delivery - Rolls	ISO 24341 (EN 426)	 25 lm (15-25 lm) x 2 m
Wear layer binder content	ISO 11638	Type 1

TECHNICAL PERFORMANCES Universe

TECHNICAL PERFORMANCES	STANDARD	Universe
Dimensional stability	ISO 23999 (EN 434)	 Requirement by standard: < 0,4 % Tarkett result: ≤ 10,021 %
Reaction to fire	EN 13501-1	 Bfl - s1
Residual indentation	ISO 24343-1 (EN 433)	 ≤ 0,10 mm
Impact sound reduction	ISO 717/2	 10 dB
Underfloor heating		 Suitable provided that the surface of the subfloor does not exceed 27°C
Fungi and bacteria resistance	EN ISO 846/2019	Does not contribute to infection spreading
Slip resistance / Ramp test	DIN 51130	R 10
Castor chair test	ISO 4918 (EN 425)	 Excellent
Furniture leg	EN 424	Pass
Light fastness	ISO 105 B02 - Method 3	≥ 6
Thermal resistance	EN 12524	0,01 - 0,02 m ² K/W
Static electrical propensity	EN 1815	≤ 2 kV (antistatic)



					Manufactured by: Tarkett d.o.o. Bačka Palanka Industrijska zona 14 21400 Bačka Palanka SERBIA
2701-0068-DoP-2021-11	This product is 100% recyclable	EN 13893	EN 1815		